

Standard Relay Racks



Features

Each frame is:


- (A) One piece welded construction made of 12 GA. C.R.S. that is tapped with 10-32 holes on the front flange.
- (B) Holes are provided in the side of the rack for ganging. Bases are provided with cut-outs for bolting units to the floor. Isolator pads and bolting kits are available.

Optional:

To order double tapped rack, add the suffix "DT" to the end of the part number. e.g. RR7019 DT







PART#	OVERALL	OVERALL	CLEARANCE	OVERALL	VERTICAL PANEL
	WIDTH	HOLES C/C	BETWEEN	HEIGHT	OPENING
			UPRIGHTS		
	"A"	"B"	"C"	"D"	"E"
RR4219	21"	18 ⁵ / ₁₆ "	17 ¹³ / ₁₆ "	47 ⁵ / ₈ "	43 ⁷ / ₈ "
RR7019	21"	18 ⁵ / ₁₆ "	17 ¹³ / ₁₆ "	75 ⁵ / ₈ "	71 ⁷ / ₈ "
RR7719	21"	18 ⁵ / ₁₆ "	17 ¹³ / ₁₆ "	82 ⁵ / ₈ "	78 ⁷ / ₈ "
RR8419	21"	18 ⁵ / ₁₆ "	17 ¹³ / ₁₆ "	89 ⁵ / ₈ "	85 ⁷ / ₈ "
RR4223	25"	22 ⁵ / ₁₆ "	21 ¹³ / ₁₆ "	47 ⁵ / ₈ "	43 ⁷ / ₈ "
RR7023	25"	22 ⁵ / ₁₆ "	21 ¹³ / ₁₆ "	75 ⁵ / ₈ "	71 ⁷ / ₈ "
RR7723	25"	22 ⁵ / ₁₆ "	21 ¹³ / ₁₆ "	82 ⁵ / ₈ "	78 ⁷ / ₈ "
RR8423	25"	22 ⁵ / ₁₆ "	21 ¹³ / ₁₆ "	89 ⁵ / ₈ "	85 ⁷ / ₈ "